

Caja de cierre NAP para Empalmes y Terminaciones



Descripción:

La caja FATC-001 de terminación y acceso para redes de fibra óptica (NAP) está diseñada para alojar hasta 16 bajadas con cable "drop"; 24 conectores SC internos y 96 protectores termocontraíbles de empalmes por fusión con cierre hermético.

Sirve como caja de cierre para empalmes por fusión y como punto de acceso con terminaciones conectorizadas y salidas independientes para los cables de bajada al abonado (Drop).

Adecuada para redes FTTx integra las funciones de alojamiento de empalmes, terminación conectorizada SC, alojamiento de splitters y distribución de conexiones en una caja de cierre de sólida construcción con fácil acceso y cierre hermético.

Características:

- Water-proof design with IP-68 Protection level.
- Integrated with flap-up splice cassette and adaptor holder.
- Impact test:IK10,Pull Force:100N,Full rugged design
- All stainless metal plate and anti-rusting bolts,nuts.
- Fiber bend radius control more than 40mm.
- Suitable for the fusion splice or mechanical splice.
- 2 pcs of 1*8 Splitter can be installed as an option.
- Mechanical sealing structure and mid-span cable entry.
- 16 ports cable entrance for drop cable.
- 24 adaptors for drop cable patching



Configuración

Material	Tamaño	Capacidad		Adaptadores	Peso	Color
Strengthen Polymer Plastic	A*B*C(mm) 385*245*130	Splice 96 Fibers (4trays, 24 fiber/tray)	PLC Splitter 2pcs of 1x8	24pcs of SC (not included)	4,5 Kg.	Black

Aplicación

- Wall mounting and pole mounting installation
- FTTH pre-installation and field installation
- 4-7mm cable ports suitable for 2x3mm indoor FTTH drop cable and outdoor figure 8 FTTH self-supporting. Standard Accessories
- Splice cassette and cable management tool, installation nuts and bolts, protection sleeves
- Hose clamp, cable tube, wrench, cover holder, rubber seal for cable entrance.

Accesorio opcional

- Pole ring